



Importmag

MAȘINĂ DE MONTAT STĂLPI

Putere motor: 38 kW

Înălțime pilon: 3100 mm

Greutate: 3000 kg



DATE TEHNICE

Dimensiuni	2750 * 2250 * 4367 mm
Debit hidraulic	60 - 100 min/l
Frecventa impactului	400 - 800 hz
Diametrul tijei de foraj	85 mm
Unghiul de înclinare a cadrului de ghidare alunecare	(Stânga) 35 (Dreapta) 10
Presiunea sistemului hidraulic	16 - 20 MPA
Debitul pompei cu angrenaje	40 - 50 min/l
Viteza de deplasare	3 km/h
Cursa de alunecare de la stânga la dreapta	0 - 450 mm



HWH380 SMALL FOUR-WHEEL PILE DRIVER

Guardrail pile driver is a product developed according to the market demand and the mature technology of its own. It adopts the new design concept, with the dust removal function, specially developed comprehensive functions, and the design concept of modular structure. The fully enclosed installation structure is more conducive to rapid product installation and moving.



Product details

Hydraulic hammer

Equipped with high-frequency hammer, featuring high impact and high frequency

Engine

Using a four-cylinder engine, featuring large power and stable performance

Rubber tires

Reinforced steel tire, with the anti-skid function and long service life

Axle

Wheel reduction bridge, Stable performance and strong carrying capacity

Main technical parameters			
Overall dimensions at work (mm)	2750*2260*4367	Sliding rail frame inclination (°)	left35right10
Overall dimensions for transportation (mm)	2750*2250*2650	Adjustable angle range (°)	±10
Hydraulic hammer model	AR85	Hydraulic system pressure (MPa)	16-20
Hydraulic hammer flow (min/l)	60-100	Gear pump flow (min/l)	40-50
Impact frequency (hz)	400-800	Travel speed (km/h)	3
Drill rod diameter (mm)	85	Sliding stroke from left to right (mm)	0-450
Traveling motor torque (Nm)	1300	Vehicle weight (kgs)	3000
Pile height (mm)	3100	Engine power (kw)	38